

FITTING INSTRUCTIONS FOR EH0051BK / EXHAUST HANGER SUZUKI GSXR 1000 L2 2012



Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away*!



Picture 1

- Remove OEM rear foot pegs/exhaust hanger.
- Place the two original bolts that secured the rear foot pegs in place through the two top holes in the R&G hanger. Then place the two spacers over the exposed threads, as shown in picture 1.
- Offer up to bike as shown above and engage threads (do not tighten yet).



- Place the 8mm washer onto the M8 x 25mm button head bolt from the kit and position through the
 exhaust mount as shown above.
- Place 8mm washer and M8 nyloc nut onto exposed end of bolt and tighten all bolts evenly.
- Please ensure when the motorcycle is being used that no parts are in such a position that they may collide/damage other bike parts (this is particularly important if using after-market cans or exhaust systems).

Please note that it is your responsibility to ensure that no part of the exhaust hanger or exhaust assembly fouls or comes into contact with other parts of the machine. Do not ride the motorcycle until this aspect has been verified and you have compressed the rear suspension (if appropriate to the design of the motorcycle) to test this thoroughly.

ISSUE 1 07/06/2012 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.



Instructions de montage

EH0051BK / Support pot d'échappement SUZUKI GSXR 1000 L2 2012



La façon dont le kit est emballé ne représente pas nécessairement la façon de le monter sur la moto.

Notez que dans les cas où les kits sont emballés avec des rondelles en caoutchouc, composantes du boulon - les rondelles en caoutchouc doivent être jetées !



Photo 1



- Enlever les repose pied d'origine/support de pot d'échappement
- Placer les 2 boulons d'origine qui fixaient les repose pied en place à travers les 2 trous du haut dans le support R&G. Ensuite, placer les 2 entretoises autour des extrémités (photo 1).
- Installer sur la moto comme indiqué ci dessus puis engager dans les filetages (Ne pas fixer à ce stade du montage).
- Placer la rondelle de 8mm sur le boulon à tête ronde M8 x 25mm du kit et positionner à travers le support de potd'échappement comme indiqué ci-dessus.
- Placer la rondelle de 8mm et l'écrou en Nyloc M8 sur l'extrémité exposée du boulon puis serrer tous les boulons de façon égale.
- Assurez vous que lorsque le moto sera utilisée, aucune partie ne sera à même d'endommager une autre partie de la moto (Surtout si vous utilisez une ligne d'échappement qui n'est pas d'origine).

Il est de votre responsabilité de veiller à ce qu'aucune partie de l'ensemble d'échappement ne puisse rentrer en contact avec une autre partie de la machine. Ne pas conduire la moto jusqu'a ce que cet aspect ait été vérifié et après avoir compresse la suspension arrière.

ISSUE 1 07/06/2012 (AR)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in resellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.