

# FITTING INSTRUCTIONS FOR CP0112BL/WH CRASH PROTECTORS YAMAHA FZR1000 '87-'93

Please note that the way the kit is packed does not necessarily represent the way of mounting to the bike

Please note that in cases where kits are packed with rubber washers holding the components onto the bolt – *the rubber washers should be thrown away*!

## Offside (right side as you sit on bike)

- Remove side fairing panel
- Undo lower engine mount bolt so that it protrudes enough to mark the inside of the panel
- Using white paint or Tippex, paint end of bolt
- Refit fairing, allowing white paint to mark inside of fairing
- Remove fairing
- Pilot drill hole back (inside) to front (outside) of fairing
- Fit fairing, make sure pilot hole lines up with centre of bolt
- Remove panel and drill 25 mm diameter hole (tank cutter is best)
- Deburr hole with sharp knife
- Remove bolt
- Slide the longer spacer into the frame recess
- Refit fairing
- Put washer onto M10 x 110 (longer) bolt, slide bolt through bobbin, through new fairing hole and through the spacer
- Tighten bolt (do not overtighten you can use Loctite or similar) until you feel the compression from inside the protector. Turn a little more so that you feel the compression increase slightly. Then apply a quarter turn. Do not overtighten as damage can occur to the bike. Do not exceed 40nm of torque.

#### •

## Nearside (left side as you sit on bike)

• Repeat as above except using the shorter (90mm) bolt & shorter spacer. There is only one available engine mount, unlike the other side of the bike

### CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorised (if not pre-authorised the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.